



# Incandescent Lamps

## T-2 Telephone Slide Base - Type 5 (short)




Part Number	Design Voltage	Amps	End Foot Candles	Life Hours	Filament Type
18ESB	18.0	.040	850	5,000	C-2F
24CSB	24.0	.017	100	15,000	C-2F
24ESB	24.0	.040	850	8,000	C-2F
28ESB	28.0	.040	1,500	6,000	C-2F
48ESB	48.0	.040	3,000	5,000	CC-2F

## T-2 Telephone Slide Base - Type 5 (standard)



Part Number	Design Voltage	Amps	End Foot Candles	Life Hours	Filament Type
6PSB	6.0	.140	550	20,000	C-2V
12PSB	12.0	.170	2,000	12,000	C-2F
24PSB	24.0	.073	3,000	10,000	C-2F
28PSB	28.0	.040	1,600	5,000	C-2F
48PSB	48.0	.053	1,800	10,000	C-7A
60PSB	60.0	.050	2,200	7,500	C-7A
120PSB	120.0	.025	1,200	5,000	CC-7A

## T-2 Telephone Slide Base - Type 3



Part Number	Design Voltage	Amps	End Foot Candles	Life Hours	Filament Type
4A	4.0	.190	450	5,000	C-2
6A	6.0	.140	510	15,000	C-2V
6B	6.0	.290	270	15,000	C-2F
6C	6.0	.040	180	4,000	C-2
8A	8.0	.090	600	1,000	C-2
10A	10.0	.110	600	5,000	C-2V
10B	10.0	.250	900	5,000	C-2F
10EX	10.0	.035	100	10,000	C-6
12A	12.0	.100	1,200	8,000	C-2F
12B	12.0	.035	650	2,000	C-6
12C	12.0	.170	1,500	5,000	C-2V
15A	15.0	.100	720	1,000	C-2F
16A	16.0	.100	720	5,000	C-2F
18A	18.0	.040	800	1,000	C-2F
18B	18.0	.100	600	10,000	C-2F
24A	24.0	.030	600	1,000	C-2F
24B	24.0	.040	1,000	4,000	C-2F
24C	24.0	.072	1,400	6,000	C-2F