

CMC 443 Series 5MM Round Threaded Plain Lens



5mm Round standard threaded plain lens

Notes

MOUNTING: Mounts in a $\text{Ø}.312\pm.002$ [$\text{Ø} 7.92\text{mm}\pm.05$] panel hole on $.500$ [12.7mm] centers. Panel thickness $.031$ [$.8\text{mm}$] to $.125$ [3.18mm]. Panel hole should be deburred, but not chamfered.

ASSEMBLY: Insert lens through panel hole, slide lock washer onto lens barrel and twist on retaining ring. PCB mounted LEDs slide into lens when the panel cover is closed or the PCB card is inserted into the case.

MATERIAL:

Lens-Polycarbonate, UL 94-V2

Lock Washer- CR Steel, Nickel plate


Retaining ring - Thermoplastic, U.L. 94-HB

This is an assembly that used the RTN_441 retainer ring

Max torque nut should be tightened to is 1.8lb-in. (Product begins to fail at 3.2lb-in.)

U.S. & Foreign Pat. Issued & Pend.

Product Dimensions



Ordering Data

ORDERING CODE : CMC 443 XXX

MODEL

LENS COLOR	
RTP	RED TRANSPARENT
ATP	AMBER TRANSPARENT
GTP	GREEN TRANSPARENT
BTP	BLUE TRANSPARENT
YTP	YELLOW TRANSPARENT
CTP	CLEAR TRANSPARENT

Compliances and Approvals

